

Model name		RTV-XG850				
Type		General purpose		Worksite		Special
Body color		Orange		Orange, Green	RealTree * AP Camouflage	Black
Engine	Type	2-cylinders, 4-cycle, Gas, DOHC				
	Displacement	cc	851			
	Horsepower	HP (kW) /rpm	48.3 (36) / 5,750			
	Cooling system		Liquid			
	Battery	Ah, CCA	56, 650			
Transmission		CVT PLUS (CVT with centrifugal clutch)				
Gear selection		Hi-Lo range forward, neutral, reverse				
Max. Traveling speed		mph (km/h)	0-40 (0-64.4)			
4WD system	Front differential	Limited-slip differential				
	Rear differential	Foot operated differential lock				
Steering		Speed sensitive Electric Power Steering				
Brakes	Front / Rear	4-wheel hydraulic disc brake				
	Parking brake	Rear wheel, hand operated				
Suspension	Front suspension	Independent, Dual A-arms with adjustable spring preload				
	Front suspension travel	in. (mm)	9 (229)			
	Rear suspension	Independent with coil over shock				
	Rear suspension travel	in. (mm)	8.5 (216)			
Ground clearance	Front	in. (mm)	9.8 (249)			
	Rear	in. (mm)	9.9 (249)			
Headlights		LED (High-Low) with 2 reflectors				
Occupant Protective System (OPS)	Tubular overhead structure	in. (mm)	2.0 (50.8)			
	Seat belts	3-point				
	Certification	SAE J2194 and OSHA ROPS standards				
Seating		2				
Dimensions	Length	in. (mm)	117 (2,973) *without bumper	119.6 (3,093) *include bumper		
	Width	in. (mm)	63.2 (1,605)			
	Height, overall	in. (mm)	79.5 (2,020) *include ROPS			
	Front tread centers	in. (mm)	52 (1,320)			
	Rear tread centers	in. (mm)	52 (1,320)			
	Wheelbase	in. (mm)	80.5 (2,045)			
	Turning radius	ft. (m)	13.1 (4.0)			
Weight		lbs. (kg)	1,761 (799) *dry			
Towing capacity		lbs. (kg)	Flat : 2,000 (907.2) / Slope : 1,550 (703)			
Payload capacity		lbs. (kg)	1,435 (651)			
Cargo bed	Material	Steel				
	Width x Length x Depth	in. (mm)	40.5 x 57.5 x 11.4 (1,030 x 1,465 x 290)			
	Volume	cu. F. (m3)	15.2 (0.43)			
	Cargo bed load	lbs. (kg)	1,000 (454) / 600 (272) *California mode			
	Dumping system	Manual				
Power Lift		Optional electric hydraulic power lift				
Fuel tank capacity		US gal (L)	8.64 (32.7)			
Sound rating at operator's ear at max rpm		db. (A)	89.8			
Tires	Front and rear	ATV	25 x 10-12, 6-ply			
		HDWS	25 x 10-12, 6-ply	Optional	25 x 10-12, 6-ply	
Front guard		Optional		Standard front guard		
Alloy wheel		Optional		Standard		
Steering tilt		Not available		Standard		
Spray-on bed liner		Not available		Optional		
				Standard		

*"Realtree®" is a registered trademark of Jordan Outdoor Enterprises, Ltd. The company reserves the right to change the above specifications without notice. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. For off-highway use only.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.